

CLAIM AMENDMENTS

1 - 11. (canceled)

1 12. (new) In combination with a power track having a
2 slot in which are exposed electrical conductors, an adapter com-
3 prising:

4 a housing having an insert part fittable into the slot;

5 a shaft extending into the insert part and pivotal about
6 a shaft axis in the housing between a use position and a nonuse
7 position

8 a conductive contact element rotationally fixed to the
9 shaft, having a contact projecting radially from the shaft and
10 engageable with one of the power-track conductors when the insert
11 part is fitted to the slot and the shaft is in the use position,
12 and having a one-piece plug-type terminal extending generally
13 parallel to the axis; and

14 a hookup wire provided with another plug-type terminal
15 mated with the contact-element terminal.

1 13. (new) The power-track adapter defined in claim 12
2 wherein the contact is unitarily formed with the contact element.

1 14. (new) The power-track adapter defined in claim 13
2 wherein the contact element is formed as a spring urging the
3 contact radially outward.

1 15. (new) The power-track adapter defined in claim 12
2 wherein the control shaft is at least partially hollow.

1 16. (new) The power-track adapter defined in claim 15
2 wherein the control shaft is formed with a throughgoing passage,
3 the adapter further comprising
4 another feed wire extending through the passage.

1 17. (new) The power-track adapter defined in claim 12,
2 further comprising
3 a second conductive contact element separate from the
4 first-mentioned contact element, rotationally fixed to the shaft,
5 having a contact projecting radially from the shaft, and engageable
6 with another of the power-track conductors when the insert part is
7 fitted to the slot and the shaft is in the use position, and having
8 a one-piece plug-type terminal extending generally parallel to the
9 axis; and
10 a second hookup wire separate from the first-mentioned
11 hookup wire and provided with a plug-type terminal mated with the
12 second contact-element terminal.

1 18. (new) The power-track adapter defined in claim 18
2 wherein the other plug-type terminal of the hookup wire is dis-
3 placeable axially in the housing for connection with and disconnec-
4 tion from the contact-element terminal.